

MATERIAL SAFETY DATA SHEET

Date of Last Revision: 1/09

GlobalTech® Lead Eliminator*

Product Code: LE

FOR CHEMICAL EMERGENCY call INFOTRAC at 1-800-535-5053
24 Hrs. per day, 7 days per week

Section 1 ... Composition/Information on Ingredients

Ingredients	CAS#	EXPOSURE LEVELS			PERCENTAGES
		PPM	Agency	Type	
Water	7732-18-5		NE		>60%
Gluconic Acid	526-95-4		NE		<40%
Compound Oil Soluable Fragrance	none (mixture)		NE		<1%

This product does not contain a substance, which must be reported under the requirements of SARA Title III-313 and 40 CFR 371

Section 2 ... First Aid Measures

Eye Contact:	If irritation or redness from vapor exposure develops, move victim away from exposure source. If symptoms persist, seek medical attention. For direct contact, hold eyelids apart and flush affected eyes(s) with clean water for 20 minutes. Seek medical attention.
Skin Contact:	Remove contaminated clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and /or persists, seek medical attention. Launder contaminated clothing before reuse.
Inhalation:	If respiratory or other overexposure symptoms develop, move victim away from exposure source into fresh air. If symptoms persist, seek immediate medical attention. If victim is not breathing, artificial respiration should be administered. If breathing difficulty is experienced, oxygen should be administered by qualified personnel. Seek medical attention.
Ingestion - Aspiration Hazard:	Do NOT induce vomiting or give anything by mouth. Vomited material can enter the lungs and cause lung damage. If victim is drowsy or unconscious, place on left side with head down. If possible, do not leave victim unattended. If victim is conscious and alert, give milk or water to dilute the contaminate.

Note to Physician: Epinephrine and other sympathomimetic drugs may potentate arrhythmia in persons exposed to this substance. Such drugs should be used cautiously, if at all, and only with cardiac monitoring. Pre-existing conditions may be aggravated by exposure.

Section 3 ... Health Hazards, Routes of Entry and Effects of Overexposure

Eye Contact:	This material will irritate eyes. Direct contact with the liquid or exposure to the vapor or mist cause tearing, stinging and redness.
Skin Contact:	This material may cause skin irritation. Prolonged or repeated exposure to this material may cause redness, burning and cracking or drying of skin. Contact may result in skin absorption, but toxicity symptoms via this route are unlikely, under normal conditions. Person with pre-existing conditions may be more susceptible to the effects of this material.
Inhalation:	While this material has a low degree of toxicity, inhaling of large amounts of mists or vapors may cause irritation of mucous membranes, nervous system depression (drowsiness, fatigue, motor coordination loss), nausea and headaches. Prolonged or repeated exposure to mists or vapor may damage peripheral nerves. Respiratory symptoms, associated with pre-existing conditions, may be exaggerated upon exposure to this material.
Ingestion:	While this material has a low degree of toxicity, ingestion of excessive amounts may cause irritation of the digestive tract. Signs of nervous system depression (dizziness, drowsiness, fatigue, motor coordination loss) and nausea may develop.

Comments: This material has not been identified as a carcinogen, or probable carcinogen by NTP, IARC or OSHA. Pre-existing peripheral nerve disorders may be aggravated by exposure to this material. Persons with pre-existing heart disorders may be more susceptible to irregular heartbeats if exposed to high concentrations of this material (see Section 2 - Note to Physician). Reports have associated repeated and/or prolonged exposure to solvents with permanent brain or nervous system damage (sometimes referred to as Solvent or Painter's Syndrome). Intentional misuse by deliberately concentrating and inhaling this material may be harmful or fatal

*patent pending

Section 10 ... Regulatory Information cont.

Section 311/312 Hazard Class - 40 CFR 370.2:

(X) Immediate () Fire (X) Delayed () Reactive () Sudden Release of Pressure

Section 313 Comp - 40 CFR 370.65: None

OSHA Process Safety Mgmt - 29 CFR 1910: None listed.

EPA Accidental Release Prevention - 40 CFR 68: None listed.

International Regulations:

Inventory Status DSL (Canada): The international ingredients of this product are listed.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

The information contained herein is based on data believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the material. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk for his use thereof. JNJ accepts no responsibility for any personal injury, property damage, or other type of loss due to negligence or otherwise resulting from the use or handling of this material.